

Widespan roller shutters slats are 55mm and are useful for areas that are too big for domestic shutter (40mm profile) and too small for commercial shutters.

The 55mm profile is a double walled cavity with PU (polyurethane) foam injected during the roll forming process. This profile is available for use on openings up to 50% larger than our standard domestic profiles while maintaining the same level of strength and insulation qualities.

The wides pan profiles are curved, which uses a minimal head box size, making it an ideal substitute for garage doors or commercial door applications where room for roll up is limited.

Suitable applications:

- Doorways
- Big windows
- Garage door

Features and benefits:

- Insulation
- Security
- Available for wider spans
- Ideal for garage doors
- Reduced greenhouse emissions
- Protection from the elements
- Light control
- Obstacle detection motor

Weight (per m2) 4KG Maximum curtain width 4.2m Maximum area (m2) 11.8 Gauge of Aluminium 0.32mm Profile Slat Height 55mm **Profile Slat Thickness** 11mm Standard Guide Dimensions 70mm Standard Bottom Bar Dimension 50mm

Technical Specifications

Motorisation

We offer systems hard wired into the building or 12V Battery operated motors. All of our motors can be synced to be operated together or separately with one or multiple remotes. Through the Somfy Connexoon App, the shutters can be opened or closed from the users phone. Whatever your automation needs, we have a solution. All of our motors meet the Australian Electrical Standards and come with the EESS Compliance Regulatory Mark.

240V Electric Automation

- 1, 5 or 15 channel remote controls
- Either wall switch or remote motors
- Remotely operated obstacle detection motors
- Push button and/or key switch operation

Battery operated motor

- Somfy wireless RTS
 - E-Port Series 12V motor with wall controller
- Shutter Supplies 12v motor with remote control

Colours













Blue

Grev



Black

Grey